













Model	Basic Series FlexScan® EV2400R	Basic Series FlexScan® EV2410R	Professional Office Series FlexScan® EV2720S	Professional Office Series FlexScan® EV2740S	Premium Series FlexScan® EV2795	Premium Series FlexScan® EV2740X	Premium Series FlexScan® EV3240X	Ultrawide Series FlexScan® EV3450XC	Ultrawide Series FlexScan® EV3895	Premium Series FlexScan® EV4340X
Panel Size Panel type * Manufactured/ Pixel pitch	23.8" IPS 16:9 0.275	24.1" IPS 16:10 0.270	27.0" Flat IPS 16:9 0.233	27.0" Flat IPS 16:9 0.155	27.0" IPS 16:9 0.233	27.0" Flat IPS 16:9 0.155	31.5" Flat IPS 16:9 0.182	34.1" Curved IPS 21:9 0.233	37.5" Curved IPS 24:10 0.229	42.5" Flat IPS 16:9 0.245
Brightness cd/m ²	350	350	350	350	350	350	350	300	300	350
Contrast Ratio Dynamic Contrast	1500:1	1300:1	1500:1	1000:1	1000:1	2000:1	2000:1	1000:1	1000:1	1000:1
Horiz. Viewing Angle (10:1)	178°	178°	178°	178°	178°	178°	178°	178°	178°	178°
Vert. Viewing Angle (10:1)	178°	178°	178°	178°	178°	178°	178°	178°	178°	178°
Optimum Resolution	1920x1080	1920x1200	2560x1440	3840x2160	2560x1440	3840x2160	3840x2160	3440x1440	3840x1600	3840x2160
Input Signals	HDMI DisplayPort	VGA, DVI-D HDMI DisplayPort	USB Type-C HDMI *2 DisplayPort	USB Type-C HDMI *2 DisplayPort	USB Type-C HDMI DisplayPort	USB Type-C HDMI *2 DisplayPort	USB Type-C HDMI *2 DisplayPort	USB Type-C HDMI *2 DisplayPort	USB Type-C HDMI *2 DisplayPort	USB Type-C HDMI *2 DisplayPort
Integrated Speakers	2 x 1W Audio In/Out	2 x 1W Audio In/Out	2 x 1W Audio In/Out	2 x 2W Audio In/Out	2 x 1W Audio In/Out	2 x 2W Audio In/Out	2 x 2W Audio In/Out	2 x 4W Audio In/Out	2 x 1W Audio In/Out	2 x 4W Audio In/Out
Video Response time typical / gray to gray	/ 5 ms	/ 5 ms	/ 5 ms	/ 6 ms	/ 5 ms	/ 5 ms	/ 5 ms	/ 5 ms	/ 5 ms	/ 5 ms
Horizontal Scan Freq (kHz)	Digital: 31 -114	Digital: 31 -76	Digital: 31 -89	Digital: 31 -134	Digital: 31 -68	Digital: 31 -134	Digital: 31 -134	Digital: 31 -89.5	Digital: 31 -89.5	Digital: 31 -134
Vertical Scan Freq (Hz)	Digital: 100Hz	Digital: 59-61	Digital: 59-61	Digital: 59-61	Digital: 59-61	Digital: 59-61	Digital: 59-61	Digital: 59-61	Digital: 59-61	Digital: 59-61
Net Weight (Kg) H//E	5.6	6.0	8.5	8.6	8.5	8.2	9.4	9.2	13.2	15.9
Physical Dimensions (W x H x D) mm	537.8 x 333.6 - 473.6 x 233	531 x 358.4 - 488.3 x 233	611.6 x 376.3 - 545.3 x 230	611.6 x 376.3 - 545.3 x 230	611.4 x 368.6 - 545.2 x 230	611.6 x 370.8 - 565.4 x 242-250	712.2 x 427.3 - 622.2 x 242-251	819.5 x 414.5 - 609.5 x 242-250	893.9 x 411 - 603.7 x 240	966.8 x 631 x 225.2
Power Consumption	8W	8W	14W	12W	16W	16W	18W	23W	28W	31W
Casing Color	Black or White	Black or White	Black or White	Black or White	Black or White	Black or White	Black or White	Black or White	Black or White	Black or White
Special Features	FlexStand Tilt, Pivot, Height Adjustment 2xUSB3.1 HUB VESA 100x100	FlexStand Tilt, Pivot, Height Adjustment 4xUSB3.1 HUB VESA 100x100	Slim. FlexStand Tilt, Pivot, Height Adjustment. USB3.1 HUB RJ45 LAN. PbyP PowerDeliv. 70W	Slim. FlexStand Tilt, Pivot, Height Adjustment. USB3.1 HUB RJ45 LAN. PbyP PowerDeliv. 70W	FlexStand Tilt, Pivot, Height Adjustment USB3.1 3*A+1*C RJ45 LAN Daisy Chain conn.	FlexStand Tilt, Pivot, Height Adjustment. USB3.1 HUB RJ45 LAN. PowerDeliv. 94W PbyP, PinP	FlexStand Tilt, Pivot, Height Adjustment. USB3.1 HUB RJ45 LAN. PowerDeliv. 94W PbyP, PinP	FlexStand Tilt, Pivot, Height Adjustment. USB3.1 HUB RJ45 LAN. PbyP Webcam 5Mp, microphone	FlexStand Tilt, Pivot, Height Adjustment. USB3.1 HUB RJ45 LAN. PbyP Daisy Chain conn.	USB3.1 HUB RJ45 LAN. PowerDeliv. 94W PbyP, PinP
המחירים בש"ח כולל מע"מ לאקדמיה	 1600	 1940	 2890	 3740	 4530	 5590	 7300	 6920	 6660*	 8550